



OpenACC introduction

Aleksei Ivakhnenko



Contents

- ⌚ Advantages of OpenACC
- ⌚ Execution model
- ⌚ OpenACC memory model
- ⌚ Directive syntax in C and Fortran
 - Main directives
- ⌚ Examples of **vector addition** and **reduction**
- ⌚ OpenACC compilers:
 - PGI for NVIDIA and Radeon GPUs
 - GCC open-source compiler
 - Examples
- ⌚ Hands-on on server
 - Connecting
 - Transferring
 - Reviewing examples



Links

Specifications v.1.0 and 2.0 are available at:

- <http://www.openacc-standard.org>

Trial version of compiler

- http://www.nvidia.com/object/openacc-toolkit.html#utm_source=shorturl&utm_medium=referrer&utm_campaign=openacctoolkit





OpenACC advantages



SAXPY example, C: OpenMP

- Simple
- Open standard
- High performance


```
void saxpy(int n, float a, float *x,
           float *restrict y){
#pragma omp parallel for
    for (int i = 0; i < n; ++i)
        y[i] = a*x[i] + y[i];
}

...
// Perform SAXPY on 1M elements
saxpy(1<<20, 2.0, x, y);
...
```



SAXPY example, C: OpenACC

- Simple
- Open standard
- High performance



```
void saxpy(int n, float a, float *x,  
          float *restrict y){  
#pragma acc parallel  
    for (int i = 0; i < n; ++i)  
        y[i] = a*x[i] + y[i];  
}  
  
...  
// Perform SAXPY on 1M elements  
saxpy(1<<20, 2.0, x, y);  
...
```



CUDA C/Fortran vs. OpenACC

CUDA C/Fortran:

- High performance of the manually optimized code
- Porting code step by step
- CUDA-capable GPU's only
- One has to support 2 versions of code

OpenACC:

- Good performance is possible
- Porting to different accelerators step by step
- One can use not only CUDA-platforms
- One version of code
- Manual optimization is limited
- Performance depends on the compiler “cleverness”



OpenACC API

Directives point out parallel regions (C & Fortran)

- Offload parallel regions to GPU
- Sources are cross-platform, cross-compiler and cross-accelerator

One can implement hybrid (CPU + ACC) high-level programs

- Without apparent accelerator initialization
- Without apparent data management



OpenACC



- ➊ Programming model allows one to program easily, providing the compiler with hints:
 - Data management
 - Loops mapping
 - Other performance details
- ➋ Interoperation with other programming languages and libraries:
 - CUDA C / Fortran
 - GPU-accelerated libraries: CUFFT, CUBLAS, CUSPARSE, ...



OpenACC Execution and Memory model



OpenACC Execution and Memory model





OpenACC Execution model



CPU

- Executes the main part of the program
- Allocates memory on the accelerator
- Copies data from the host memory
- Sends the code to the accelerator
- Waits until the end of the kernel execution
- Copies the results back to the host memory
- Frees the accelerator memory



Accelerator

- Executes kernels
- Can transfer data asynchronously with the execution



OpenACC Execution model

- ➊ 3 levels of parallelism: **gang, worker, vector**
- ➋ Mapped to an architecture as a set of processing elements (PEs)
- ➌ Each PE consists of workers, each worker is capable to execute vector instructions
- ➍ Mapping to an accelerator architecture is up to compiler (may be tracked via the output of compiler)



OpenACC API



Directive syntax

Fortran

`!$acc directive [clause [, clause] ...]`

structured block

`!$acc end directive`

C

`#pragma acc directive [clause [, clause] ...]`

structured block

Compiling (with PGI compiler)

`pgfortran -acc -Minfo=accel -ta=nvidia <filename>`

`pgcc -acc -Minfo=accel -ta=nvidia <filename>`



Parallel construct

Fortran

```
!$acc parallel [clause [, clause]...]
```

Structured block

```
!$acc end parallel
```

When the program encounters an accelerator parallel construct, one or more gangs are created to execute the accelerator parallel region

C

```
#pragma acc parallel [clause [, clause]...]
```

Structured block



Parallel clauses

Main clauses

- ⌚ if (condition)
- ⌚ async [(exp)]
- ⌚ num_gangs (exp)
- ⌚ num_workers (exp)
- ⌚ vector_length(exp)
- ⌚ reduction(operator:list)

Data clauses

- ⌚ copy*(list)
- ⌚ create(list)
- ⌚ present(list)
- ⌚ present_or_copy*(list)
- ⌚ present_or_create(list)
- ⌚ deviceptr(list)
- ⌚ private(list)
- ⌚ firstprivate(list)

*<blank>|in|out



Restrictions

- ➊ Can't have conditional entry- and leaving-points inside
- ➋ Should not depend on the clauses order
- ➌ Only one 'if' clause allowed
- ➍ Only the `async`, `wait`, `num_gangs`, `num_workers`, and `vector_length` clauses may follow a `device_type` clause



Kernels Construct

Fortran

```
!$acc kernels [clause [, clause]...]
```

Structured block

```
!$acc end kernels
```

This construct defines a region of the program that is to be compiled into a sequence of kernels for execution on the accelerator device.

C

```
#pragma acc kernels [clause [, clause]...]
```

Structured block



```
#pragma acc kernels
```

```
{  
    for (int i= 0; i<n; i++)  
    {  
        for (int j = 0; j<n; j++)  
        {  
            a[i][j] = 0;  
        }  
    }  
}
```

Kernel 1

```
    for (int k = 0; k<n; k++)  
    {  
        b[k] = 1;  
    }  
}
```

Kernel 2

Kernels Construct

The compiler will split the code in the kernels region into a sequence of accelerator kernels. Typically, each loop nest will be a distinct kernel.



Clauses

Main clauses

- ⌚ if (condition)
- ⌚ async [(exp)]

Data clauses

- ⌚ copy*(list)
- ⌚ create(list)
- ⌚ present(list)
- ⌚ present_or_copy*(list)
- ⌚ present_or_create(list)
- ⌚ deviceptr(list)
- ⌚ private(list)
- ⌚ firstprivate(list)

*<blank>|in|out



Loop Construct

Fortran

```
!$acc loop [clause [, clause]...]
    do loop
```

C

```
#pragma acc loop [clause [, clause]...]
    for loop
```

Clauses

- collapse(n)
- gang[(exp)]
- worker[(exp)]
- vector[(exp)]
- seq
- independent
- private(list)
- reduction(op:list)



Vector addition

- Vector addition is “Hello world!” of parallel computing
- Takes **2** vectors (same size)
- Returns **1** resulting vector (same size)

$$C_0 = A_0 + B_0$$

$$C_1 = A_1 + B_1$$

.....

$$C_{n-1} = A_{n-1} + B_{n-1}$$



```
int n=1000;  
float a[n], b[n], c[n];
```

```
for (int i=0; i<n; i++)  
{  
    a[i]=(float)rand()/RAND_MAX;  
    b[i]=(float)rand()/RAND_MAX;  
}
```

Initialization

```
for (int i=0; i<n; i++)  
{  
    c[i]=a[i]+b[i];  
}
```

Parallel region.
Data cells are
independent

$$C_0 = A_0 + B_0$$

$$C_1 = A_1 + B_1$$

• • • • • • • • • • • • • • •

$$C_{n-1} = A_{n-1} + B_{n-1}$$

Example: Vector addition



```
int n=1000;  
float a[n], b[n], c[n];
```

```
for (int i=0; i<n; i++)  
{  
    a[i]=(float)rand()/RAND_MAX;  
    b[i]=(float)rand()/RAND_MAX;  
}
```

Initialization

```
#pragma acc parallel loop independent  
for (int i=0; i<n; i++)  
{  
    c[i]=a[i]+b[i];  
}
```

Parallel region.
Data cells are
independent

Example: Vector addition

$$C_0 = A_0 + B_0$$

$$C_1 = A_1 + B_1$$

• • • • • • • • • • • • • • • •

$$C_{n-1} = A_{n-1} + B_{n-1}$$



```
int n=1000;  
float a[n], b[n], c[n];
```

```
for (int i=0; i<n; i++)  
{  
    a[i]=(float)rand()/RAND_MAX;  
    b[i]=(float)rand()/RAND_MAX;  
}
```

Initialization

```
#pragma omp target map (to:a,b), map (from:c)  
#pragma omp parallel for  
for (int i=0; i<n; i++)  
{  
    c[i]=a[i]+b[i];  
}
```

Parallel region.
Data cells are
independent

Example: Vector addition OpenMP

$$C_0 = A_0 + B_0$$

$$C_1 = A_1 + B_1$$

• •

$$C_{n-1} = A_{n-1} + B_{n-1}$$



Example: Vector addition CUDA

```
int n=1024;
float a[n], b[n], c[n];
float *da, *db, *dc;
cudaMalloc(da,sizeof(float)*n);
cudaMalloc(db,sizeof(float)*n);
cudaMalloc(dc,sizeof(float)*n);
for (int i=0; i<n; i++)
{
    a[i]=(float)rand()/RAND_MAX;
    b[i]=(float)rand()/RAND_MAX;
}
cudaMemcpy(da, a, sizeof(float)*n, cudaMemcpyHostToDevice);
cudaMemcpy(db, b, sizeof(float)*n, cudaMemcpyHostToDevice);
vecAdd<<<n/32,32>>>(da,db,dc,n);
cudaMemcpy(c, dc, sizeof(float)*n, cudaMemcpyDeviceToHost);
cudaFree(da);
cudaFree(db);
cudaFree(dc);
```




Example: Vector addition CUDA

```
__global__ void vecadd(float* a, float *b, float *c, int n)
{
    idx=threadIdx.x+blockIds.x*blockDim.x;
    if (idx<n)
    {
        c[idx]=a[idx]+b[idx];
    }
}
```



Example: Reduction

- Unlike vector addition, simple reduction takes only **1** vector and “operator”
- Returns **1** scalar
- Operator could be mathematical, logic operator, function (e.g. max) etc.
- Reduction is characterized by complex data dependency






Example: Reduction

```
int n=1000;  
float a[n];  
float b=0;  
for (int i=0; i<n; i++)    Initialization  
{  
    a[i]=(float)rand()/RAND_MAX;  
}
```

```
for (int i=0; i<n; i++)  
{  
    b+=a[i];  
}  
std::cout<<b[i]<<"\n";
```


Parallel region.
Complex data dependency





Example: Reduction

```
int n=1000;
float a[n];
float b=0;
for (int i=0; i<n; i++)    Initialization
{
    a[i]=(float)rand()/RAND_MAX;
}
```



```
#pragma acc parallel reduction (+:b)
for (int i=0; i<n; i++)
{
    b+=a[i];
}
std::cout<<b[i]<<"\n";
```

Parallel region.
Complex data
dependency




```
int n=1000;  
float a[n];  
float b=0;  
for (int i=0; i<n; i++)  
{  
    a[i]=(float)rand()/RAND_MAX;  
}
```

Initialization

```
#pragma omp target map(to:a), map(from:b)  
#pragma omp parallel for reduction(+:b)  
for (int i=0; i<n; i++)  
{  
    b+=a[i];  
}  
std::cout<<b[i]<<"\n";
```

Parallel region.
Complex data
dependency



Example: Reduction OpenMP



Example: Reduction CUDA

```
template <unsigned int blockSize>
__global__ void reduce(int *g_idata, int *g_odata, unsigned int n)
{
extern __shared__ int sdata[];
unsigned int tid = threadIdx.x;
unsigned int i = blockIdx.x*(blockSize*2) + tid; unsigned int gridSize =
blockSize*2*gridDim.x; sdata[tid] = 0;
while (i < n)
{
    sdata[tid] += g_idata[i] + g_idata[i+blockSize];
    i += gridSize;
}
__syncthreads();
if (blockSize >= 512)
{
    if (tid < 256)
    {
        sdata[tid] += sdata[tid + 256];
    }
    __syncthreads()
} if (blockSize >= 256)
{
    if (tid < 128)
    {
        sdata[tid] += sdata[tid + 128];
    } __syncthreads();
}
```



```
if (blockSize >= 128)
{
    if (tid < 64)
    {
        sdata[tid] += sdata[tid + 64];
    }
    __syncthreads();
}
if (tid < 32)
{
    if (blockSize >= 64)
        sdata[tid] += sdata[tid + 32];
    if (blockSize >= 32)
        sdata[tid] += sdata[tid + 16];
    if (blockSize >= 16)
        sdata[tid] += sdata[tid + 8];
    if (blockSize >= 8)
        sdata[tid] += sdata[tid + 4];
    if (blockSize >= 4)
        sdata[tid] += sdata[tid + 2];
    if (blockSize >= 2)
        sdata[tid] += sdata[tid + 1];
}
if (tid == 0) g_odata[blockIdx.x] = sdata[0];
}
```

Example: Reduction CUDA



OpenACC Compilers



OpenACC compliers

- There are different compilers for OpenACC code including PGI, PathScale, CRAY, CAPS.
- Despite OpenACC is an open standard, almost all compilers are non-free (even now after 4 years).
- GCC 5.0 introduced OpenACC support, but it's very limited yet.
- PGI (owned by NVIDIA) is one of the most advanced compilers. Not so long ago it received **free academic license** and **90 day trial license**.



Parallel vs. Kernels

```
int a [1000];
int b [1000];
#pragma acc parallel
{
    for (int i=0; i<1000; i++)
        a[i] = i - 100 + 23;

    for (int j=0; j<1000; j++)
        b[j] = j - 10 + 213;
}
```



Parallel vs. Kernels

```
pgcc parallel.c -acc -Minfo=accel -ta=nvidia,time -o parallel
parallel.c:
main:
```

10, Accelerator kernel generated

Generating Tesla code

12, #pragma acc loop vector(128) /* threadIdx.x */

16, #pragma acc loop vector(128) /* threadIdx.x */

10, Generating copyout(a[:,],b[:,])

12, Loop is parallelizable

16, Loop is parallelizable



Parallel vs. Kernels

```
int a [1000];
int b [1000];
#pragma acc kernels
{
    for (int i=0; i<1000; i++)
        a[i] = i - 100 + 23;

    for (int j=0; j<1000; j++)
        b[j] = j - 10 + 213;
}
```



Parallel vs. Kernels

```
pgcc kernels.c -acc -Minfo=accel -ta=nvidia,time -o kernels
kernels.c:
main:
  10, Generating copyout(a[:,],b[:])
  12, Loop is parallelizable
    Accelerator kernel generated
    Generating Tesla code
    12, #pragma acc loop gang, vector(128) /* blockIdx.x threadIdx.x */
  16, Loop is parallelizable
    Accelerator kernel generated
    Generating Tesla code
    16, #pragma acc loop gang, vector(128) /* blockIdx.x threadIdx.x */
```



GCC limitations

- ⌚ GCC 5 includes a preliminary implementation of the OpenACC2.0a specification.
- ⌚ The execution model currently only allows for one gang, one worker, and a number of vectors. These vectors will all execute in "vector-redundant" mode. This means that inside a parallel construct, offloaded code outside of any loop construct will be executed by all vectors, not just a single vector. The reduction clause is not yet supported with the parallel construct.
- ⌚ The kernels construct so far is supported only in a simplistic way: the code will be offloaded, but execute with just one gang, one worker, one vector. No directives are currently supported inside kernels constructs. Reductions are not yet supported inside kernels constructs.
- ⌚ The atomic, cache, declare, host_data, and routine directives are not yet supported.
- ⌚ The default(None), device_type, firstprivate, and private clauses are not yet supported. A parallel construct's implicit data attributes for scalar data types will be treated as present_or_copy instead of firstprivate. Only the collapse clause is currently supported for loop constructs, and there is incomplete support for the reduction clause.
- ⌚ Combined directives (kernels loop, parallel loop) are not yet supported; use kernels alone, or parallel followed by loop, instead.
- ⌚ Nested parallelism (cf. CUDA dynamic parallelism) is not yet supported.
- ⌚ Usage of OpenACC constructs inside multithreaded contexts (such as created by OpenMP, or pthread programming) is not yet supported.
- ⌚ <https://gcc.gnu.org/wiki/OpenACC>



Parallel (gcc)

```
int a [1000];
int b [1000];
#pragma acc parallel
{
    for (int i=0; i<1000; i++)
        a[i] = i - 100 + 23;

    for (int j=0; j<1000; j++)
        b[j] = j - 10 + 213;
}
```



Parallel vs. Kernels

```
/opt/gcc-5.2.0_offload/usr/local/bin/gcc parallel.c -fopenacc -o parallel
aivahnenko@tesla-cmc:/scratch/aivahnenko/openacc/gcc/examples/parallel$ ./parallel
libgomp: num_gangs (4) different from one is not yet supported
```

- GCC now only starts OpenACC support so it can be used for studying OpenACC, but doesn't give any good performance.
- GCC has a lot of restrictions and can't be used for big projects yet.



Independent vs. Seq

```
int a [10000];

#pragma acc kernels
{
    #pragma acc loop independent
    for (int i=0; i<100; i++)
    {
        #pragma acc loop independent
        for (int j=0; j<100; j++)
            a[i*100 + j] = i - 100 + 23 + j;
    }
}
```



Independent vs. Seq

```
pgcc independent.c -acc -Minfo=accel -ta=nvidia,time -o independent
independent.c:
```

```
main:
```

```
  9, Generating copy(a[:])
 12, Loop is parallelizable
 15, Loop is parallelizable
 Accelerator kernel generated
 Generating Tesla code
 12, #pragma acc loop gang /* blockIdx.y */
 15, #pragma acc loop gang, vector(128) /* blockIdx.x threadIdx.x */
```



Independent vs. Seq

```
int a [10000];

#pragma acc kernels
{
    #pragma acc loop independent
    for (int i=0; i<100; i++)
    {
        #pragma acc loop seq
        for (int j=0; j<100; j++)
            a[i*100 + j] = i - 100 + 23 + j;
    }
}
```



Independent vs. Seq

```
pgcc seq.c -acc -Minfo=accel -ta=nvidia,time -o seq
```

```
seq.c:
```

```
main:
```

```
  9, Generating copy(a[:])
```

```
 12, Loop is parallelizable
```

```
 15, Loop is parallelizable
```

```
 Accelerator kernel generated
```

```
 Generating Tesla code
```

```
 12, #pragma acc loop gang, vector(128) /* blockIdx.x threadIdx.x */
```



Example



Example

```
//Jacobi solver
while (eps > tolerance)
{
    change = 0.0f;
    iter++;
//Parallel region to be executed on GPU
    for (int j = 1; j < n-1; j++)
    {
        for (int i = 1, i < n-1; i++)
        {
            newa[i][j] = w0 * a[i][j] +
                         w1 * (a[i-1][j] + a[i][j-1] + a[i+1][j] + a[i][j+1]) +
                         w2 * (a[i-1][j-1] + a[i-1][j+1] + a[i+1][j-1] + a[i+1][j+1]);
            eps = max(eps, abs(newa[i][j] - a[i][j]));
        }
    }
    swap(a, newa);
//end of parallel region
}
```



Example

```
//Jacobi solver
while (eps > tolerance)
{
    change = 0.0f;
    iter++;
#pragma acc parallel
{
    for (int j = 1; j < n-1; j++)
    {
        for (int i = 1, i < n-1; i++)
        {
            newa[i][j] = w0 * a[i][j] +
                w1 * (a[i-1][j] + a[i][j-1] + a[i+1][j] + a[i][j+1]) +
                w2 * (a[i-1][j-1] + a[i-1][j+1] + a[i+1][j-1] + a[i+1][j+1]);
            eps = max(eps, abs(newa[i][j] - a[i][j]));
        }
    }
    swap(a, newa);
}
```



Example

```
#pragma acc data copy(a, newa)
{
while (eps> tolerance)
{
    change = 0.0f;
    iter++;
#pragma acc parallel reduction (max:eps)
{
    for (int j = 1; j<n-1; j++)
    {
        for (int i = 1, i<n-1; i++)
        {
            newa[i][j]= w0 * a[i][j] +
                w1 * (a[i-1][j] +a[i][j-1]+a[i+1][j]+a[i][j+1]) +
                w2 * (a[i-1][j-1]+a[i-1][j+1]+a[i+1][j-1]+a[i+1][j+1]);
            eps = max(eps, abs(newa[i][j] - a[i][j]));
        }
    }
    swap(a,newa);
}
}
```



Example

```
#pragma acc data copyin(a) create(newa)
{
while (eps> tolerance)
{
    change = 0.0f;
    iter++;
#pragma acc parallel reduction (max:eps)
{
    for (int j = 1; j<n-1; j++)
    {
        for (int i = 1, i<n-1; i++)
        {
            newa[i][j]= w0 * a[i][j] +
                w1 * (a[i-1][j] +a[i][j-1]+a[i+1][j]+a[i][j+1]) +
                w2 * (a[i-1][j-1]+a[i-1][j+1]+a[i+1][j-1]+a[i+1][j+1]);
            eps = max(eps, abs(newa[i][j] - a[i][j]));
        }
    }
    swap(a,newa);
}
}
```



Example

```
#pragma acc data copyin(a) create(newa)
{
while (eps> tolerance)
{
    change = 0.0f;
    iter++;
#pragma acc parallel reduction (max:eps), vector_length (256)
{
    for (int j = 1; j<n-1; j++)
    {
        for (int i = 1, i<n-1; i++)
        {
            newa[i][j]= w0 * a[i][j] +
                w1 * (a[i-1][j] +a[i][j-1]+a[i+1][j]+a[i][j+1]) +
                w2 * (a[i-1][j-1]+a[i-1][j+1]+a[i+1][j-1]+a[i+1][j+1]);
            eps = max(eps, abs(newa[i][j] - a[i][j]));
        }
    }
    swap(a,newa);
}
}
```



Example

Tesla T10 Processor

```
$ ./jacobi.acc 1024
reached delta= 0.09998 in      3430 iterations for 1024 x 1024 array
time = 25.8760 seconds
```

Intel(R) Xeon(R) CPU E5620 @2.40GHz

```
$ ./jacobi 1024
reached delta= 0.09998 in      3430 iterations for 1024 x 1024 array
time(host) = 140.386185 seconds
```



Example

	N=400	N=512	N=1024
CPU One-thread	6.7759	16.0250	140.3861
OpenMP	1.8580	3.7771	29.6452
PGI OpenACC	6.8860	8.9890	9.2995
CUDA C (manually optimized)	3.8095	4.1140	6.5899



Questions?

Aleksei Ivakhnenko
ivakhnenko@parallel-computing.pro

Useful links:

<http://parallel-compute.com>

<http://www.openacc-standard.org>

<http://www.pgroup.com/resources/accel.htm>

<http://developer.nvidia.com/category/zone/cuda-zone>